



A Division of SAE Corporation

Nortek® COPPERWORKS

PO Box 118, Pembine, WI 54156

(888) 488-2380

Fax: (715) 324-5754

info@nortekcopperworks.com

www.nortekcopperworks.com

Outlast™ Inside Satin and Inside Lo-Glos (Water Based, Water Clean-Up!)

- ◆ Satins available in clear, light toner and medium toner
- ◆ Lo-Glos available in clear only
- ◆ For Interior log walls, trim, cabinetry, paneling
- ◆ Enhances the natural wood grain
- ◆ Seals Out Household odors (Cooking and Fireplace odors)
- ◆ Unique water-based formulation is VOC compliant, quick drying,
- ◆ Retards surface mildew growth, provides a water repellent easy to clean surface

Outlast Inside Satin is the premier interior treatment designed with log home wall and trim surfaces in mind. Available in clear, light and medium toners, the finish is “tough as nails”, but allows interior log moisture vapor to escape without clouding the finish.

Outlast Inside Lo-Glos provides all the benefits of Inside Satin in a low gloss sheen. Use over Inside Satin when a glossier look is desired. Excellent for kitchen cabinets, trim work, doors and more.

Always test the finish before use, because the only way to remove this durable coating is to sand it off. Never OVER apply Outlast Inside Satin or Inside Lo-Glos. The product will look milky in the can and slightly milky when applied, but it dries crystal clear. One gallon will cover 400 square feet of smooth wood. Stir gently but thoroughly before use. Avoid application temperatures below 40 degrees. Airless spray is an appropriate application method for delivery to broad expanses of interior wall or ceiling surfaces **when selecting the clear colorless product only**. We recommend that the light and medium toners be applied by brush. Smooth out any runs quickly – This product dries FAST! Always keep a wet edge when using the light or medium toners to avoid lap marks. When rolling, use a short nap roller. If a second coat is desired, lightly sand and re-coat after 3 hours drying time.


Surface Preparation: Even if the wood looks clean, always wash with water and a small amount of detergent and bleach if mildew is present. Wipe until clean with plain water. (Remove all bleach residue.) For fastest (and quick rinse-away) cleaning of mildew stains and dirt, use Outlast KleenStart for surface prep. If desired, lightly sand and vacuum before application. DO NOT USE steel wool. We highly recommend that the interior air conditioning or heating systems be turned on and operational for at



PO Box 118
 Pembine, WI 54156
 (888) 488-2380
 Fax: (715) 324-5754
 Date: May 15, 2008

Inside Satin

info@nortekcopperworks.com
 www.nortekcopperworks.com



For spill, leak, or Medical Emergency call Infotrac 800-535-5053

Section I - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	%(optional)
None Present				

Section II - Physical/Chemical Characteristics

Boiling Point	> 212° F	Specific Gravity (H ₂ O = 1)	1.06
Vapor Pressure (mm Hg.)	Unknown	Melting Point	@ 32° F
Vapor Density (AIR = 1)	Unknown	Evaporation Rate (Water = 1)	1
Solubility in Water: Dispersible	VOC: 0.26 #'s/gallon 31.7 grams/liter		
Appearance and Odor: Milky mobile liquid with mild odor	Shipping Information: Resin Solution, Non Hazmat, Class 55 NMFC = 149980		

Section III - Fire and Explosion Hazard Data

Flash Point (Method Used) Non-flammable	Flammable Limits	LEL N/A	UEL N/A
Extinguishing Media: As appropriate for surrounding fire.			
Special Fire Fighting Procedures: Use water spray to cool containers exposed to fire.			
Unusual Fire and Explosion Hazards: This material will not burn or support combustion unless and until all of the water component has boiled away.			

Section IV - Reactivity Data

Stability	Unstable		Conditions to Avoid: Can react with strong acids or hypochlorite bleach.
	Stable	X	
Incompatibility (<i>Materials to Avoid</i>) Non Known			
Hazardous Decomposition or Byproducts None Known			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section V - Health Hazard Data

Route(s) of Entry:	Inhalation? Yes	Skin? Yes	Ingestion? Yes
Health Hazards (<i>Acute and Chronic</i>): May be irritating to sensitive tissues and mucous membranes. <u>Inhalation</u> : Excessive inhalation of mist can cause mild irritation. Higher concentrations of mist may cause burns, tissue damage, and irritation of upper respiratory tract. <u>Eye contact</u> : Inside Satin and can cause burns that result in damage to the eyes. <u>Contact with the skin</u> : Inside Satin can cause irritation if not rinsed from the skin. <u>Ingestion</u> : If swallowed, can cause gastric upset.			
Carcinogenicity:	NTP? No	IARC Monographs No?	OSHA Regulated? No

Inside Satin (cont'd)

Section V - Health Hazard Data (cont'd)

Signs and Symptoms of Exposure: Irritation of the skin, eyes, mouth, and/or mucous membranes. The mist from this product can cause respiratory irritation.

Medical Conditions Generally Aggravated by Exposure: Existing dermatitis or conjunctivitis

Emergency and First Aid Procedures

Eyes: Irrigate eyes with water for at least 15 to 20 minutes. Seek medical attention immediately. Skin: Wash contaminated areas with plenty of water. Remove contaminated clothing and footwear and wash clothing before reuse. Discard footwear which cannot be decontaminated. Seek medical attention if irritation persists or if blistering is present. Inhalation: Get person out of contaminated area to fresh air. If breathing has stopped, resuscitate and administer oxygen if readily available. Seek medical attention immediately. Ingestion: Never give anything by mouth to an unconscious person. If swallowed, **do not** induce vomiting. Give large quantities of water. If available, give several glasses of milk. If vomiting occurs spontaneously, keep airways clear. Seek medical attention immediately.

Section VI - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

Spill Cleanup Procedures: For small spill flush with ample water. For large spills: First contain the spill—pick up and reuse as much product as is practical. Rinse the area and pick up the water for disposal. Waste Disposal: Do not allow product to contact waterways. Dispose in conformance with federal, state and local regulations. Environmental Hazards: This material is considered to be biodegradable. However, some components of this mixture can be harmful to fish and other wildlife. Use in such a way that runoff does not contact streams or open waterways.

Precautions to Be taken in Handling and Storing

Store in closed containers between 50° F – 120° F.
Keep away from excessive heat.
Store and use in well ventilated areas.
Drum is not a pressure vessel; never use pressure to empty.

Section VII - Control Measures

Respiratory Protection (*Specify Type*)

In confined spaces or other circumstances where adequate ventilation cannot be assured use NIOSH-approved respirator, positive pressure airline mask, or self contained breathing apparatus.

Ventilation	Local Exhaust Suitable for almost all applications	Special
	Mechanical (<i>General</i>)	Other

Protective Gloves Rubber or neoprene	Eye Protection Safety goggles & face shield where appropriate.
---	---

Other Protective Clothing or Equipment

Use of a rubber or neoprene apron is highly recommended if the product is being used in such a way that it might contact the skin

Work/Hygienic Practices

Normal Industrial Hygiene Practices. Keep out of the reach of children.